




**VALVES**

**Mini Ball Valve - Male / Female**



Part No.	Part No.	D	DN	I	L	G	A	H	CH
VMMF02R	VMMF02B	1/8"	5	10	41,5	22	22,5	31	21
VMMF04R	VMMF04B	1/4"	8	11	41,5	22	22,5	31	21
VMMF06R	VMMF06B	3/8"	8	11	41,5	22	22,5	31	21
VMMF08R	VMMF08B	1/2"	10	13	49	22	22,5	31	25

**Mini Ball Valve - Female / Female**



Part No.	Part No.	D	DN	I	L	G	A	H	CH
VM02R	VM02B	1/8"	6	10	41,5	22	22,5	31	21
VM04R	VM04B	1/4"	8	11	41,5	22	22,5	31	21
VM06R	VM06B	3/8"	8	11	41,5	22	22,5	31	21
VM08R	VM08B	1/2"	10	13	49	26	22,5	31	25

**Quality:**

- Dual sealing system allows valve to be operated in either direction making installation easier.
- No metal-to-metal moving parts.
- No maintenance ever required.
- Handle clearly shows ball position.
- Silicone-free lubricant on all seals.
- Chrome plated brass ball for longer life.
- Each valve is seal tested for maximum safety.

**Body:**

- One piece drawn sand blasted brass body with an extreme compact design.
- Finest brass according to EN 12164 specification.
- Patent n. 7011-B/89.

**Thread:**

- ISO 7/1, BS21 Male thread: BSPT – Female thread: BSPP.

**Stem:**

- Blowout-proof brass stem with FPM O-ring.

**Handle:**

- Metal Handle removable with valve in service.

**Seals:**

- Pure PTFE self-lubricating seats with flexible-lip design.

**Working Pressure:**

- 30 Bar (450 PSI).

**Operating Temperature:**

- +120°C (+248°F).

