


SOCKET HEAD CAP SCREWS

Socket Head Cap Screws



d	M1,6	M2	M2,5	M3	M4	M5	M6	M8	M10	M12	M14	M16	M18	M20	M24
Thread-pitch	0,35	0,40	0,45	0,50	0,70	0,80	1,00	1,25	1,50	1,75	2,00	2,00	2,50	2,50	3,00
D	3	3,8	4,5	5,5	7	8,5	10	13	16	18	21	24	27	30	36
k	1,6	2	2,5	3	4	5	6	8	10	12	14	16	18	20	24
b	15	16	17	18	20	22	24	28	32	36	40	44	48	52	60
s	1,5	1,5	2	2,5	3	4	5	6	8	10	12	14	14	17	19

Length	Thread Size Metric														
	1,6	2	2,5	3	4	5	6	8	10	12	14	16	18	20	24
3		*													
4	*	*													
5		*	*	*	*										
6	*	*	*	*	*	*									
8		*	*	*	*	*	*								
10		*	*	*	*	*	*	*	*						
12		*	*	*	*	*	*	*	*	*					
14			*	*	*	*	*	*	*	*	*				
15			*	*	*	*	*	*	*	*	*	*			
16			*	*	*	*	*	*	*	*	*	*	*		
18			*	*	*	*	*	*	*	*	*	*	*	*	
20			*	*	*	*	*	*	*	*	*	*	*	*	*
22			*	*	*	*	*	*	*	*	*	*	*	*	*
25			*	*	*	*	*	*	*	*	*	*	*	*	*
30			*	*	*	*	*	*	*	*	*	*	*	*	*
35			*	*	*	*	*	*	*	*	*	*	*	*	*
40			*	*	*	*	*	*	*	*	*	*	*	*	*
45			*	*	*	*	*	*	*	*	*	*	*	*	*
50			*	*	*	*	*	*	*	*	*	*	*	*	*
55			*	*	*	*	*	*	*	*	*	*	*	*	*
60			*	*	*	*	*	*	*	*	*	*	*	*	*
65			*	*	*	*	*	*	*	*	*	*	*	*	*
70			*	*	*	*	*	*	*	*	*	*	*	*	*
75			*	*	*	*	*	*	*	*	*	*	*	*	*
80			*	*	*	*	*	*	*	*	*	*	*	*	*
90			*	*	*	*	*	*	*	*	*	*	*	*	*
100			*	*	*	*	*	*	*	*	*	*	*	*	*
110			*	*	*	*	*	*	*	*	*	*	*	*	*
120			*	*	*	*	*	*	*	*	*	*	*	*	*
130			*	*	*	*	*	*	*	*	*	*	*	*	*
140			*	*	*	*	*	*	*	*	*	*	*	*	*
150			*	*	*	*	*	*	*	*	*	*	*	*	*
160			*	*	*	*	*	*	*	*	*	*	*	*	*
180			*	*	*	*	*	*	*	*	*	*	*	*	*
200			*	*	*	*	*	*	*	*	*	*	*	*	*

Material: High tensile strength (12.9).
DIN 912/ISO 4762.

Order example

HCS-(Thread Size+(-)+Length) ex. HCS-16-35 (M16x35mm).